



SAFETY DATA SHEET RT156BE RESIN

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RT156BE RESIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Resintech Ltd
Unit 1-2 Horcott Industrial Estate
Fairford
Gloucestershire
UK
Tel: +44 (0)1285 712755
Fax: +44 (0)1285 712999
info@resintech.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1285 712755 (Monday-Friday 8am-4.30pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

RT156BE RESIN

Precautionary statements	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	<p>EUH205 Contains epoxy constituents. May produce an allergic reaction.</p> <p>EUH210 Safety data sheet available on request.</p>
Contains	Bis-[4-(2,3-epoxipropoxi)phenyl]propane, formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, oxirane, mono[(C12-14-alkyloxy)methyl] derivs
Supplementary precautionary statements	<p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Bis-[4-(2,3-epoxipropoxi)phenyl]propane		70-100%
CAS number: 1675-54-3 EC number: 216-823-5		
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		
formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol		5-10%
CAS number: 9003-36-5 EC number: 500-006-8		
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		

RT156BE RESIN

oxirane, mono[(C12-14-alkyloxy)methyl] derivs		1-5%
CAS number: 68609-97-2	EC number: 271-846-8	
Classification		
Skin Irrit. 2 - H315		
Skin Sens. 1 - H317		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin contact	Remove contamination with soap and water or recognised skin cleansing agent. Remove contaminated clothing. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause sensitisation or allergic reactions in sensitive individuals.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

RT156BE RESIN

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Phenolics. Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Immiscible with water. Avoid release to the environment. Absorb spillage with non-combustible, absorbent material. Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

RT156BE RESIN

Usage precautions	Read and follow manufacturer's recommendations. Persons susceptible to allergic reactions should not handle this product. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent. Product may crystallise or separate if exposed to cold temperatures for extended periods of time. If this occurs, the product should be warmed to 38-60°C for one hour. If the product is in a bulk form stir until clear.
Storage class	Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

No exposure limits known for ingredient(s).

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

No exposure limits known for ingredient(s).

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

No exposure limits known for ingredient(s).

Bis-[4-(2,3-epoxipropoxy)phenyl]propane (CAS: 1675-54-3)

DNEL	General population - Oral; Long term systemic effects: 0.75 mg/kg, bw/day General population - Dermal; Long term, Short term systemic effects: 3.571 mg/kg, bw/day Workers - Dermal; Short term, Long term systemic effects: 8.33 mg/kg, bw/day Workers - Inhalation; Short term, Long term systemic effects: 12.25 mg/m³
PNEC	Fresh water; 0.006 mg/l marine water; 0.0006 mg/l Intermittent release; 0.018 mg/l Sediment (Freshwater); 0.996 mg/kg Sediment (Marinewater); 0.0996 mg/kg Soil; 0.196 mg/kg STP; 10 mg/l

RT156BE RESIN

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (CAS: 9003-36-5)

DNEL

Workers - Dermal; Short term local effects: 0.0083 mg/m³
 Workers - Dermal; Long term systemic effects: 104.15 mg/kg
 Workers - Inhalation; Long term systemic effects: 29.39 mg/m³
 Consumer - Dermal; Long term systemic effects: 62.5 mg/kg
 Consumer - Inhalation; Long term systemic effects: 8.7 mg/m³
 Consumer - Oral; Long term systemic effects: 6.25 mg/kg

PNEC

Fresh water; 0.003 mg/l
 marine water; 0.0003 mg/l
 STP; 10 mg/l
 Sediment (Freshwater); 0.294 mg/kg
 Sediment (Marinewater); 0.0294 mg/kg
 Intermittent release; 0.0254 mg/l
 Soil; 0.237
 STP; 10 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Gloves made from the following material may provide suitable chemical protection: Butyl rubber. Nitrile rubber. Neoprene. Rubber (natural, latex). Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. The breakthrough time for any glove material may be different for different glove manufacturers. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

RT156BE RESIN

Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use should be used.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Blue.
Odour	Mild.
Initial boiling point and range	>150°C Estimated value.
Flash point	> 100°C Closed cup. Estimated value.
Relative density	1.16 @ 20°C
Solubility(ies)	Insoluble in water.

9.2. Other information

Other information	No information required.
--------------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	See the other subsections of this section for further details.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No potentially hazardous reactions known.
---	---

10.4. Conditions to avoid

Conditions to avoid	Static electricity and formation of sparks must be prevented.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong alkalis. Oxidising materials. Strong acids. Amines.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Phenolics. Oxides of carbon.
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

RT156BE RESIN

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 544.86

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause skin sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.

Eye contact Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

RT156BE RESIN

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Acute toxicity - oral

Notes (oral LD₅₀) >1,500 mg/kg, Oral, Mouse

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Notes (dermal LD₅₀) 23032 mg/kg, Dermal, Rabbit

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Acute toxicity - oral

Notes (oral LD₅₀) >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) >2000 mg/kg, Dermal, Rat

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Acute toxicity - oral

Notes (oral LD₅₀) 19,200 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) >4500 mg/kg, Dermal, Rabbit

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 2 mg/l, Fish
Estimated value.

Acute toxicity - aquatic invertebrates LC₅₀, 48 hours: 1.8 mg/l, Daphnia magna
Estimated value.

Acute toxicity - aquatic plants LC₅₀, 72 hours: 11 mg/l, Scenedesmus subspicatus
Estimated value.

Ecological information on ingredients.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 2 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1.8 mg/l, Daphnia magna

RT156BE RESIN

Acute toxicity - aquatic plants EC₅₀, 72 hours: 11 mg/l, Scenedesmus subspicatus

Acute toxicity - microorganisms IC₅₀, 3 hours: >100 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.3 mg/l, Daphnia magna

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 0.55 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 72 hours: 1.6 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 1.8 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms IC₅₀, 3 hours: >100 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.3 mg/l, Daphnia magna

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Acute aquatic toxicity

Acute toxicity - aquatic invertebrates EC₅₀, : 10 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability Not readily biodegradable.

Ecological information on ingredients.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Persistence and degradability Not readily biodegradable.

Stability (hydrolysis) pH4 - DT₅₀ : 4.83 days @ 25°C
pH7 - DT₅₀ : 3.58 days @ 25°C
pH9 - DT₅₀ : 7.1 days @ 25°C

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Persistence and degradability The product is not biodegradable.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Persistence and degradability Not readily biodegradable.

RT156BE RESIN

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely.

Ecological information on ingredients.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 3.242 (25°C)

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 2.7 - 3.6 (25°C)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is insoluble in water. The product is non-volatile.

Ecological information on ingredients.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Adsorption/desorption coefficient - Koc: 445 @ 20°C

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Adsorption/desorption coefficient Soil - Koc: 4460 @ 20°C

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

formaldehyde,oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

RT156BE RESIN

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9

RT156BE RESIN

ICAO class/division 9

ADN class 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-A, S-F

ADR transport category 3

Emergency Action Code •3Z

Hazard Identification Number 90
(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

RT156BE RESIN

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
	ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
	RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
	IATA: International Air Transport Association.
	ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
	IMDG: International Maritime Dangerous Goods.
	CAS: Chemical Abstracts Service.
	ATE: Acute Toxicity Estimate.
	LC50: Lethal Concentration to 50 % of a test population.
	LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).
	EC ₅₀ : 50% of maximal Effective Concentration.
	PBT: Persistent, Bioaccumulative and Toxic substance.
	vPvB: Very Persistent and Very Bioaccumulative.
Classification abbreviations and acronyms	Eye Irrit. = Eye irritation
	Skin Irrit. = Skin irritation
	Skin Sens. = Skin sensitisation
	Aquatic Chronic = Hazardous to the aquatic environment (chronic)
Classification procedures according to SI 2019 No. 720	Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Calculation method. Aquatic Chronic 2 - H411: : Calculation method.
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision date	04/02/2021
Revision	9
Supersedes date	03/06/2020
SDS number	4755
Hazard statements in full	H302 Harmful if swallowed.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.