

# RT380



## Light Weight Epoxy Resin System

### Description

RT380 is a very low-density epoxy resin system for use where weight is critical.

### Benefits

- Contains advanced light weight fillers which do not impair performance
- Excellent electrical properties
- Good chemical resistance to solvents, oils, fuels, acids and bases
- Excellent mechanical properties with low cure shrinkage
- Good thermal insulation properties
- Available in easy-to-use TwinPacks or bulk

### Typical Properties

#### Curing (100g mass)

Work life at 23°C:	1 hour
Cure time at 23°C:	24 hours
Cure time at 60°C:	4 hours

#### Typical Performance (measurements at 23°C)

Mixed viscosity	11 Pa s
Density	0.6
Shore Hardness	40 D
Tensile Strength	4 MPa
Crush Resistance	50 MPa
Operating Temperature	-55°C to 150°C
Short Term	200°C
Fluid Resistance:	excellent to Fuels, Lubricating Oils, Acids and Bases good to Hydraulic Fluids, Solvents

### Colour

Black

### Related Products

- The Resintech range of potting epoxies
- RT370 flame retarded epoxy resin system

Issue 5 - April 2005

Resintech Limited warrants only that its products meet the specifications stated herein. Typical properties where stated are to be considered as representative of the current production and should not be treated as specifications. While the information presented is believed to be true and reliable, users are advised to conduct sufficient investigations to ensure the suitability of any product for its intended use. Resintech Limited cannot accept any responsibility for loss or damage that may result from the use of this information.

**Resintech Limited**

**Horcott Industrial Estate, Fairford, Gloucestershire, GL7 4BX, United Kingdom**

**t: +44 (0)1285 712755 f: +44 (0)1285 712999 e: technical@resintech.co.uk w: www.resintech.co.uk**